PHILIPS

WT238C G2 LED70S/840
PSD L1500 TW GM

911401835088



GreenPerform Waterproof Tubular G2, 43.5 W, 7000 lm, 4000 K, DALI

GreenPerform Waterproof Tubular G2 delivers on the GreenPerform promise of innovative, high-quality luminaires. A reliable, efficient luminaire with long lifetime, GreenPerform Waterproof Tubular G2 comes in two versions to meet various applications needs. The ammonia-resistant and sealed luminaire (PMMA) is suitable for animal lighting, livestock and food applications, while the PC version offers a modern and industrial design that is suitable for a wide range of general lighting applications. Both versions come with significant dust, water and impact protection

Warnings and Safety

- UV radiation will damage the material over time resulting in loss of waterproof sealing and IP rating.
- Do not install the luminaire in locations where it will be exposed to direct sunlight.

General Information

Light source engine type	LED
Value ladder	Performance

Light Technical

Luminous Flux	7,000 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	161 lm/W
Color rendering index (CRI)	80
Light source color	840 neutral white
Unified glare rating CEN	30

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Power Consumption	43.5 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	21
Protection class IEC	Safety class I

Controls and Dimming

Dimmable	Yes
Control interface	DALI

Mechanical and Housing

Housing Material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	White RAL 9003
Optical cover finish	Opal
Ingress protection code	IP68 [Dust penetration-protected, pressure watertight]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Optical cover type	Polycarbonate Diffuser
Net Weight (Piece)	1.680 kg

Approval and Application

CE mark	Yes
Ambient temperature range	-20 to +40 °C


Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	WT238C G2 LED70S/840 PSD L1500 TW GM
Full product name	WT238C G2 LED70S/840 PSD L1500 TW GM
Full product code	872110333286899
Order code	911401835088
Material Nr. (12NC)	911401835088
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8721103332868
Numerator - Packs per outer box	6
EAN/UPC - Case	8721103332974

Dimensional drawing



Related Documents

Documents and certificates	Document Name	Download
Installation Instructions	GreenPerform-Waterproof-Tubular-G2-WT238C-GM-INI.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	WT238C-G2-LED70S840-PSD-L1500-TW-GM.ies	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.