PHILIPS

**BN005C LED40/WW L1200 PSU GM**

911401899384



# Essential Smartbright Wide Batten BN005C, 40 W, 3800 lm, 3000 K, Symmetrical

Philips Essential smartbright wide batten offers exceptional value. It is Perfect for your everyday lighting installations. Available in 2 standard sizes, it has option of 3 CCTs to suit different requirements.

## General Information

| | |
|---|---|
| Number of gear units | 1 unit |
| Gear | EB [Electronic] |
| Driver included | Yes |
| Light source engine type | LED |
| Value ladder | Value |
| Warranty period | 2 years |

## Light Technical

| | |
|---|---|
| Luminous Flux | 3,800 lm |
| Correlated Color Temperature (Nom) | 3000 K |
| Luminous Efficacy (rated) (Nom) | 95 lm/W |
| Color rendering index (CRI) | ≥80 |
| Number of light sources | 1 |
| Beam angle of light source | 115 degree(s) |
| Light source color | 830 warm white |
| Optic type | Symmetrical |
| Luminaire light beam spread | 115° |
| Unified glare rating CEN | Not applicable |
| Effective projected area | 0.75 $m^2$ |

## Operating and Electrical

| | |
|---|---|
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 or 60 Hz |
| Inrush current | 39 A |
| Inrush time | 0.026 ms |
| Power Consumption | 40 W |
| Power Factor (Fraction) | 0.9 |
| Connection | - |
| Cable | Cable 0.2 m without plug |

| | |
|---|---|
| Number of products on MCB of 16 A type B | 48 |
| Suitable for random switching | No |
| Protection class IEC | Safety class II |

## Controls and Dimming

| | |
|---|---|
| Dimmable | - |
| Control interface | - |
| Maximum dim level | Not applicable |

## Mechanical and Housing

| | |
|---|---|
| Housing Material | Polycarbonate |
| Reflector material | - |
| Optic material | Polycarbonate |
| Optical cover material | Polycarbonate |
| Housing Color | White |
| Mounting device | Mounting bracket |
| Optical cover finish | - |
| Overall length | 1,200 mm |
| Overall width | 70 mm |
| Overall height | 27 mm |
| Dimensions (Height x Width x Depth) | 27 x 70 x 1200 mm |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| Optical cover type | Opal |
| Net Weight (Piece) | 0.250 kg |

## Approval and Application

| | |
|---|---|
| Glow-wire test | Temperature 650 °C, duration 30 s |
| Flammability mark | For mounting on normally flammable surfaces |
| CE mark | No |
| ENEC mark | - |
| Photobiological risk | Photobiological risk group 1 @200mm to EN62778 |
| Photobiological risk specification | 0.2 m |
| EU RoHS compliant | Yes |
| Performance ambient temperature Tq | 25 °C |
| Ambient temperature range | -20 to +40 °C |


## Initial Performance (IEC Compliant)

| | |
|---|---|
| Luminous flux tolerance | -10% / +10% |
| Initial chromaticity | (0.43, 0.40) SDCM≤6 |
| Power consumption tolerance | +/-10% |

## Product Data

| | |
|---|---|
| Order product name | BN005C LED40/WW L1200 PSU GM |
| Full product name | BN005C LED40/WW L1200 PSU GM |
| Full product code | 871951496189099 |
| Order code | 911401899384 |
| Material Nr. (12NC) | 911401899384 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8719514961890 |
| Numerator - Packs per outer box | 40 |
| EAN/UPC - Case | 8719514962019 |

## Dimensional drawing




## Related Documents

| Documents and certificates | Document Name | Download |
|---|---|---|
| Installation Instructions | ESB-BN005C-MI.pdf | Download |

| Photometry and lighting design | Document Name | Download |
|---|---|---|
| IES File | BN005C-LED40-WW-L1200-PSU.ies | Download |

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.