PHILIPS

RS280 G2 RC Rd D75 11W 30K 24D

929004120010



Semi-deep Recessed Family, 11 W, 950 lm, 3000 K, Metallic grey

Plastic, Metallic grey, 950 lm, 11 W, 86 lm/W, 3000 K, (0.4359, 0.3963) 5SDCM, IP20 | Finger-protected, IK03 | 0.35 J reinforced, Safety class II, Flying leads/wires

General Information

Light source replaceable	No
Driver included	Yes
Warranty period	1 years

Light Technical

Luminous Flux	950 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	86 lm/W
Color rendering index (CRI)	90
Light source color	930 warm white
Luminaire light beam spread	24°
Unified glare rating CEN	13

Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Inrush current	12 A
Power Consumption	11 W
Power Factor (Fraction)	0.5
Connection	Flying leads/wires
Number of products on MCB of 16 A type B	88
Protection class IEC	Safety class II

Controls and Dimming

Dimmable	No
Constant light output	No

Mechanical and Housing

Housing Material	Plastic
Reflector material	-
Housing Color	Metallic grey
Overall height	77 mm
Overall diameter	85 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.35 J reinforced]
Net Weight (Piece)	0.176 kg


Approval and Application

Insulation Coverage Rating	Non IC Rating
Flammability mark	For mounting on normally flammable surfaces
EU RoHS compliant	Yes
Ambient temperature range	-20 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.4359, 0.3963) 5SDCM
Power consumption tolerance	+/-10%

Dimensional drawing




Over Time Performance (IEC Compliant)

Median useful life L70B50	25,000 hour(s)

Product Data

Order product name	RS280 G2 RC Rd D75 11W 30K 24D
Full product name	RS280 G2 RC Rd D75 11W 30K 24D
Full product code	694197061752900
Order code	929004120010
Material Nr. (12NC)	929004120010
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6941970617529
Numerator - Packs per outer box	12
EAN/UPC - Case	6941970617536

Photometric data



Light Distribution Diagram - RS280 G2 RC Rd D75 11W 30K 24D

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-Philips-Semi-deep-R-spotlight-90030118G82924158-COMF-9423808-Ref-929004120110-20240903-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	RS280-G2-RC-Rd-D75-11W-30K-24D-IES.ies	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.