PHILIPS

**BVS211 LED195/857**
**150W 220-240V GC**

911401902479



# Bright Star BVS211/BVS221, 150 W, 20250 lm, 5700 K, Fixed Output

Philips Bright Star is a linear lighting solution designed specifically for indoor recreational sports venues, providing bright, anti-glare, and energy-efficient white light to enhance visibility and visual comfort for facilities such as badminton courts. Featuring a sleek, streamlined design, Bright Star provides clean, continuous illumination ideal for court lighting. Its one-piece stamped steel backplate guarantees structural strength, while the front optical design effectively controls glare in the direction of movement—perfectly balancing aesthetics and performance. With versatile installation options—including wall mount, suspension, and V-type dual-hanging adjustable-angle accessories—Bright Star offers flexible deployment to meet diverse lighting needs. This high-performance linear luminaire combines modern design, reliability, and superior lighting quality for an engaging indoor recreational sports experience.

## General Information

| | |
|---|---|
| Driver included | Yes |
| Light source engine type | LED |

## Light Technical

| | |
|---|---|
| Luminous Flux | 20,250 lm |
| Correlated Color Temperature (Nom) | 5700 K |
| Luminous Efficacy (rated) (Nom) | 135 lm/W |
| Color rendering index (CRI) | 80 |
| Beam angle of light source | 90 degree(s) |
| Light source color | 857 daylight |
| Unified glare rating CEN | 24 |

## Operating and Electrical

| | |
|---|---|
| Input Voltage | 220-240 V |
| Line Frequency | 50 to 60 Hz |
| Power Consumption | 150 W |
| Power Factor (Fraction) | 0.95 |
| Connection | Flying leads/wires |
| Cable | Cable 1.0 m without plug |
| Number of products on MCB of 16 A type B | 3 |
| Protection class IEC | Safety class I |

## Controls and Dimming

| | |
|---|---|
| Dimmable | No |
| Control interface | Fixed Output |

## Mechanical and Housing

| | |
|---|---|
| Housing Material | Metal |
| Optical cover material | Polystyrene |
| Housing Color | White RAL 9003 |
| Optical cover finish | Microprismatic lens |
| Ingress protection code | IP40 [Wire-protected] |
| Mech. impact protection code | IK03 [0.3 J] |
| Optical cover type | Microprismatic cover |
| Net Weight (Piece) | 2.800 kg |

## Approval and Application

| | |
|---|---|
| CE mark | No |
| Ambient temperature range | -20 to +45 °C |

## Initial Performance (IEC Compliant)

| | |
|---|---|
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-10% |

## Product Data

| | |
|---|---|
| Order product name | BVS211 LED195/857 150W 220-240V GC |
| Full product name | BVS211 LED195/857 150W 220-240V GC |
| Order code | 911401902479 |
| Material Nr. (12NC) | 911401902479 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 6941970622905 |
| Numerator - Packs per outer box | 2 |
| EAN/UPC - Case | 6941970622905 |

## Dimensional drawing




## Related Documents

| Photometry and lighting design | Document Name | Download |
|---|---|---|
| IES File | BVS211-LED195-857-150W-220-240V-GC.ies | Download |

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.