PHILIPS

Lighting



# FlexCove G5: create beautiful coving with flexible, tunable and energy-efficient LED strip lighting

## Flex Cove G5

Philips FlexCove G5 is the latest generation of our popular LED cove lighting. This comprehensive new family of flexible strip lights are designed to follow straight lines or curves to create beautiful ambiances that highlight architectural details in tunable white or colored light. These customizable cove lighting strips also promise excellent energy-saving performance, superb lighting uniformity, and color consistency. All with a long lifetime that promises less lumen decay or color shifts. So with FlexCove G5, you can flex your accent lighting to suit the requirements of any project - beautifully.

**Benefits**

- Energy-efficient LED cove lighting
- Flexible design for straight lines or curves
- Excellent lighting uniformity with color consistency
- A long lifetime of quality and reliability

**Features**

- Up to 140lm/W for energy-efficient performance
- 400lm – 2000lm options available, both with a choice of CRI 80 or CRI 90
- Standard Deviation Color Matching (SDCM) 3
- 30,000 hours lifetime @L70 B50
- Tunable white and RGB+W versions available

# Flex Cove G5

## Application

- Hospitality
- Offices
- Retail

## Specifications

| | |
|---|---|
| **Type** | LS170S G2 - Basic version |
| | LS170S PRO - PRO version with higher lm/W and more LED qty./m |
| **Mounting type** | Surface Mounted and accessory available |
| | recessed with selected mounting accessory |
| **Operating Temperature range** | -25 to +45ºC |
| **Light Source** | LED 2835 |
| **Mains Voltage** | 24VDC |
| **Mechanical Accessories** | various mounting bracket parts |
| | including surface mount and recessed. |
| **Electrical Accessories** | connector with leader cable |
| | connectors |
| **Dimming** | Driver to be ordered separately |
| | PSU: non-dimmable |
| | PSR: 1-10V |
| | PSD: DALI |
| **Control system input** | external driver to be ordered separately: DALI / 1-10V / DMX |
| **Luminous flux** | 420~450lm @830,1m length |
| | 800~820lm @830,1m length |
| | 840~880lm @830,1m length |
| | 1200~1250lm @830,1m length |
| | 1600~1650lm @830,1m length |
| | 2000lm @830,1m length |
| | 2000lm @940, 1m length |

| | |
|---|---|
| **Power consumption** | 3.4W ~ 16.5W per meter |
| **Luminaire efficacy** | Up to 140lm/W, depending on congifuration |
| **Correlated color temperature - CCT** | 827, 830, 840, 927, 930, 940, RGBW, Tunable White(2700K-6500K & 2200K-4000K) |
| **Color Rendering index - CRI** | CRI80, CRI90 |
| **Optical cover/lens finish** | Linear diffuser as accessory included in the mounting accessory kit. |
| **Protection Class IEC61140** | Class III |
| **Mechanical impact protection** | IK03 |
| **Ingress protection** | IP20 / IP44 |
| **Light source replaceable** | No |
| **Driver replaceable** | Yes, external driver to be ordered separately |
| **Overall length** | 5000mm per roll |
| **Warranty** | 3yrs |

## Versions



**Flex Cove G5**

# Flex Cove G5

## Dimensional drawing

















# Flex Cove G5

## Dimensional drawing









| Operating and Electrical | |
|---|---|
| **Protection class IEC** | Safety class III |
| **Input Voltage** | 24 DC V |
| **Line Frequency** | - Hz |
| **Controls and Dimming** | |
| **Dimmable** | Yes - Check ballast compatibility |
| **Mechanical and Housing** | |
| **Optical cover type** | Without lens |
| **Housing Color** | - |
| **Mech. impact protection code** | IK03 |
| **Approval and Application** | |
| **Ambient temperature range** | -20 to +45 °C |
| **CE mark** | No |
| **Initial Performance (IEC Compliant)** | |
| **Luminous flux tolerance** | -10% / +10% |

## Light Technical

| Order Code | Full Product Name | Correlated Color Temperature (Nom) | Color rendering index (CRI) | Luminous Efficacy (rated) (Nom) | Luminous Flux |
|---|---|---|---|---|---|
| 911401553642 | LS170S LED4 827 IP44 L5000 G2 | 2700 K | >80 | 102 lm/W | 400 lm |
| 911401553742 | LS170S LED4 840 IP44 L5000 G2 | 4000 K | >80 | 109 lm/W | 425 lm |
| 911401554042 | LS170S LED8 827 IP44 L5000 G2 | 2700 K | >80 | 98 lm/W | 745 lm |
| 911401554142 | LS170S LED8 840 IP44 L5000 G2 | 4000 K | >80 | 105 lm/W | 800 lm |
| 911401556442 | LS170S LED8 827 IP44 L5000 PRO | 2700 K | >80 | 113 lm/W | 770 lm |
| 911401556542 | LS170S LED8 830 IP44 L5000 PRO | 3000 K | >80 | 117 lm/W | 795 lm |
| 911401556642 | LS170S LED8 840 IP44 L5000 PRO | 4000 K | >80 | 121 lm/W | 830 lm |
| 911401521642 | LS170S LED20 930 IP20 L5000 HE PRO L | 3000 K | >90 | 140 lm/W | 2,000 lm |
| 911401521742 | LS170S LED20 940 IP20 L5000 HE PRO L | 4000 K | >90 | 142 lm/W | 2,050 lm |
| 911401528642 | LS170S LED12 865 IP20 L5000 G2 | 6500 K | >80 | 108 lm/W | 1,250 lm |
| 911401528742 | LS170S LED12 930 IP20 L5000 G2 | 3000 K | >90 | 88 lm/W | 1,020 lm |

| Order Code | Full Product Name | Correlated Color Temperature (Nom) | Color rendering index (CRI) | Luminous Efficacy (rated) (Nom) | Luminous Flux |
|---|---|---|---|---|---|
| 911401528842 | LS170S LED12 940 IP20 L5000 G2 | 4000 K | >90 | 92 lm/W | 1,060 lm |
| 911401554242 | LS170S LED8 S 827 IP20 L5000 G2 | 2700 K | >80 | 105 lm/W | 815 lm |
| 911401554342 | LS170S LED8 S 840 IP20 L5000 G2 | 4000 K | >80 | 112 lm/W | 875 lm |
| 911401554442 | LS170S LED8 S 927 IP20 L5000 G2 | 2700 K | >90 | 89 lm/W | 695 lm |
| 911401554842 | LS170S LED12 827 IP20 L5000 G2 | 2700 K | >80 | 101 lm/W | 1,165 lm |
| 911401554942 | LS170S LED12 840 IP20 L5000 G2 | 4000 K | >80 | 108 lm/W | 1,250 lm |
| 911401555142 | LS170S LED12 927 IP20 L5000 G2 | 2700 K | >90 | 86 lm/W | 990 lm |
| 911401555742 | LS170S LED16 827 IP20 L5000 G2 | 2700 K | >80 | 100 lm/W | 1,550 lm |
| 911401555842 | LS170S LED16 840 IP20 L5000 G2 | 4000 K | >80 | 107 lm/W | 1,665 lm |
| 911401556742 | LS170S LED8 S 827 IP20 L5000 PRO | 2700 K | >80 | 125 lm/W | 850 lm |
| 911401556842 | LS170S LED8 S 830 IP20 L5000 PRO | 3000 K | >80 | 130 lm/W | 880 lm |
| 911401556942 | LS170S LED8 S 840 IP20 L5000 PRO | 4000 K | >80 | 135 lm/W | 915 lm |
| 911401557042 | LS170S LED8 S 927 IP20 L5000 PRO | 2700 K | >90 | 106 lm/W | 725 lm |
| 911401557142 | LS170S LED8 S 930 IP20 L5000 PRO | 3000 K | >90 | 109 lm/W | 745 lm |
| 911401557742 | LS170S LED12 827 IP20 L5000 PRO | 2700 K | >80 | 121 lm/W | 1,210 lm |
| 911401557842 | LS170S LED12 830 IP20 L5000 PRO | 3000 K | >80 | 125 lm/W | 1,250 lm |
| 911401557942 | LS170S LED12 840 IP20 L5000 PRO | 4000 K | >80 | 130 lm/W | 1,300 lm |
| 911401558042 | LS170S LED12 927 IP20 L5000 PRO | 2700 K | >90 | 103 lm/W | 1,030 lm |
| 911401558142 | LS170S LED12 930 IP20 L5000 PRO | 3000 K | >90 | 106 lm/W | 1,060 lm |
| 911401558742 | LS170S LED16 827 IP20 L5000 PRO | 2700 K | >80 | 117 lm/W | 1,600 lm |
| 911401558842 | LS170S LED16 830 IP20 L5000 PRO | 3000 K | >80 | 125 lm/W | 1,650 lm |
| 911401558942 | LS170S LED16 840 IP20 L5000 PRO | 4000 K | >80 | 126 lm/W | 1,715 lm |
| 911401559042 | LS170S LED16 927 IP20 L5000 PRO | 2700 K | >90 | 100 lm/W | 1,360 lm |
| 911401559142 | LS170S LED16 930 IP20 L5000 PRO | 3000 K | >90 | 103 lm/W | 1,400 lm |
| 911401559742 | LS170S LED20 927 IP20 L5000 PRO | 2700 K | >90 | 103 lm/W | 1,700 lm |

| Order Code | Full Product Name | Correlated Color Temperature (Nom) | Color rendering index (CRI) | Luminous Efficacy (rated) (Nom) | Luminous Flux |
|---|---|---|---|---|---|
| 911401559842 | LS170S LED20 930 IP20 L5000 PRO | 3000 K | >90 | 106 lm/W | 1,750 lm |
| 911401560542 | LS170S LED8 RGBW IP44 L5000 PRO | - | - | 65 lm/W | 820 lm |
| 911401554542 | LS170S LED8 S 827 IP44 L5000 G2 | 2700 K | >80 | 101 lm/W | 790 lm |
| 911401554642 | LS170S LED8 S 840 IP44 L5000 G2 | 4000 K | >80 | 108 lm/W | 850 lm |
| 911401554742 | LS170S LED8 S 927 IP44 L5000 G2 | 2700 K | >90 | 85 lm/W | 670 lm |
| 911401555442 | LS170S LED12 827 IP44 L5000 G2 | 2700 K | >80 | 98 lm/W | 1,125 lm |
| 911401555542 | LS170S LED12 840 IP44 L5000 G2 | 4000 K | >80 | 105 lm/W | 1,205 lm |
| 911401555642 | LS170S LED12 927 IP44 L5000 G2 | 2700 K | >90 | 83 lm/W | 955 lm |
| 911401555942 | LS170S LED16 827 IP44 L5000 G2 | 2700 K | >80 | 97 lm/W | 1,500 lm |
| 911401556042 | LS170S LED16 840 IP44 L5000 G2 | 4000 K | >80 | 104 lm/W | 1,610 lm |
| 911401557242 | LS170S LED8 S 827 IP44 L5000 PRO | 2700 K | >80 | 121 lm/W | 825 lm |
| 911401557342 | LS170S LED8 S 830 IP44 L5000 PRO | 3000 K | >80 | 125 lm/W | 850 lm |
| 911401557442 | LS170S LED8 S 840 IP44 L5000 PRO | 4000 K | >80 | 130 lm/W | 885 lm |
| 911401557542 | LS170S LED8 S 927 IP44 L5000 PRO | 2700 K | >90 | 103 lm/W | 700 lm |
| 911401557642 | LS170S LED8 S 930 IP44 L5000 PRO | 3000 K | >90 | 106 lm/W | 720 lm |
| 911401558242 | LS170S LED12 827 IP44 L5000 PRO | 2700 K | >80 | 117 lm/W | 1,175 lm |
| 911401558342 | LS170S LED12 830 IP44 L5000 PRO | 3000 K | >80 | 121 lm/W | 1,210 lm |
| 911401558442 | LS170S LED12 840 IP44 L5000 PRO | 4000 K | >80 | 126 lm/W | 1,260 lm |
| 911401558542 | LS170S LED12 927 IP44 L5000 PRO | 2700 K | >90 | 100 lm/W | 1,000 lm |
| 911401558642 | LS170S LED12 930 IP44 L5000 PRO | 3000 K | >90 | 103 lm/W | 1,030 lm |
| 911401559242 | LS170S LED16 827 IP44 L5000 PRO | 2700 K | >80 | 114 lm/W | 1,550 lm |
| 911401559342 | LS170S LED16 830 IP44 L5000 PRO | 3000 K | >80 | 117 lm/W | 1,600 lm |
| 911401559442 | LS170S LED16 840 IP44 L5000 PRO | 4000 K | >80 | 122 lm/W | 1,665 lm |
| 911401559542 | LS170S LED16 927 IP44 L5000 PRO | 2700 K | >90 | 100 lm/W | 1,360 lm |
| 911401559642 | LS170S LED16 930 IP44 L5000 PRO | 3000 K | >90 | 100 lm/W | 1,360 lm |

| Order Code | Full Product Name | Correlated Color Temperature (Nom) | Color rendering index (CRI) | Luminous Efficacy (rated) (Nom) | Luminous Flux |
|---|---|---|---|---|---|
| 911401559942 | LS170S LED20 927 IP44 L5000 PRO | 2700 K | >90 | 100 lm/W | 1,650 lm |
| 911401560042 | LS170S LED20 930 IP44 L5000 PRO | 3000 K | >90 | 102 lm/W | 1,690 lm |
| 911401560342 | LS170S LED9 TNW IP44 L5000 PRO | - | - | 105 lm/W | 950 lm |
| 911401560442 | LS170S LED10 TNW IP44 L5000 PRO | - | - | 110 lm/W | 1,000 lm |
| 911401553442 | LS170S LED4 827 IP20 L5000 G2 | 2700 K | >80 | 105 lm/W | 405 lm |
| 911401553542 | LS170S LED4 840 IP20 L5000 G2 | 4000 K | >80 | 112 lm/W | 435 lm |
| 911401553842 | LS170S LED8 827 IP20 L5000 G2 | 2700 K | >80 | 102 lm/W | 775 lm |
| 911401553942 | LS170S LED8 840 IP20 L5000 G2 | 4000 K | >80 | 109 lm/W | 830 lm |

## Operating and Electrical

| Order Code | Full Product Name | Power Consumption |
|---|---|---|
| 911401553642 | LS170S LED4 827 IP44 L5000 G2 | 18.5 W |
| 911401553742 | LS170S LED4 840 IP44 L5000 G2 | 18.5 W |
| 911401554042 | LS170S LED8 827 IP44 L5000 G2 | 34 W |
| 911401554142 | LS170S LED8 840 IP44 L5000 G2 | 34 W |
| 911401556442 | LS170S LED8 827 IP44 L5000 PRO | 29.5 W |
| 911401556542 | LS170S LED8 830 IP44 L5000 PRO | 29.5 W |
| 911401556642 | LS170S LED8 840 IP44 L5000 PRO | 29.5 W |
| 911401521642 | LS170S LED20 930 IP20 L5000 HE PRO L | 60 W |
| 911401521742 | LS170S LED20 940 IP20 L5000 HE PRO L | 60 W |
| 911401528642 | LS170S LED12 865 IP20 L5000 G2 | 49 W |
| 911401528742 | LS170S LED12 930 IP20 L5000 G2 | 49 W |
| 911401528842 | LS170S LED12 940 IP20 L5000 G2 | 49 W |
| 911401554242 | LS170S LED8 S 827 IP20 L5000 G2 | 35 W |
| 911401554342 | LS170S LED8 S 840 IP20 L5000 G2 | 35 W |
| 911401554442 | LS170S LED8 S 927 IP20 L5000 G2 | 35 W |
| 911401554842 | LS170S LED12 827 IP20 L5000 G2 | 49 W |
| 911401554942 | LS170S LED12 840 IP20 L5000 G2 | 49 W |
| 911401555142 | LS170S LED12 927 IP20 L5000 G2 | 49 W |
| 911401555742 | LS170S LED16 827 IP20 L5000 G2 | 63 W |
| 911401555842 | LS170S LED16 840 IP20 L5000 G2 | 63 W |
| 911401556742 | LS170S LED8 S 827 IP20 L5000 PRO | 30 W |
| 911401556842 | LS170S LED8 S 830 IP20 L5000 PRO | 30 W |
| 911401556942 | LS170S LED8 S 840 IP20 L5000 PRO | 30 W |
| 911401557042 | LS170S LED8 S 927 IP20 L5000 PRO | 30 W |
| 911401557142 | LS170S LED8 S 930 IP20 L5000 PRO | 30 W |
| 911401557742 | LS170S LED12 827 IP20 L5000 PRO | 41 W |
| 911401557842 | LS170S LED12 830 IP20 L5000 PRO | 41 W |
| 911401557942 | LS170S LED12 840 IP20 L5000 PRO | 41 W |
| 911401558042 | LS170S LED12 927 IP20 L5000 PRO | 41 W |
| 911401558142 | LS170S LED12 930 IP20 L5000 PRO | 41 W |

| Order Code | Full Product Name | Power Consumption |
|---|---|---|
| 911401558742 | LS170S LED16 827 IP20 L5000 PRO | 52 W |
| 911401558842 | LS170S LED16 830 IP20 L5000 PRO | 52 W |
| 911401558942 | LS170S LED16 840 IP20 L5000 PRO | 52 W |
| 911401559042 | LS170S LED16 927 IP20 L5000 PRO | 52 W |
| 911401559142 | LS170S LED16 930 IP20 L5000 PRO | 52 W |
| 911401559742 | LS170S LED20 927 IP20 L5000 PRO | 65 W |
| 911401559842 | LS170S LED20 930 IP20 L5000 PRO | 65 W |
| 911401560542 | LS170S LED8 RGBW IP44 L5000 PRO | 48 W |
| 911401554542 | LS170S LED8 S 827 IP44 L5000 G2 | 35 W |
| 911401554642 | LS170S LED8 S 840 IP44 L5000 G2 | 35 W |
| 911401554742 | LS170S LED8 S 927 IP44 L5000 G2 | 35 W |
| 911401555442 | LS170S LED12 827 IP44 L5000 G2 | 49 W |
| 911401555542 | LS170S LED12 840 IP44 L5000 G2 | 49 W |
| 911401555642 | LS170S LED12 927 IP44 L5000 G2 | 49 W |
| 911401555942 | LS170S LED16 827 IP44 L5000 G2 | 63 W |
| 911401556042 | LS170S LED16 840 IP44 L5000 G2 | 63 W |
| 911401557242 | LS170S LED8 S 827 IP44 L5000 PRO | 30 W |
| 911401557342 | LS170S LED8 S 830 IP44 L5000 PRO | 30 W |
| 911401557442 | LS170S LED8 S 840 IP44 L5000 PRO | 30 W |
| 911401557542 | LS170S LED8 S 927 IP44 L5000 PRO | 30 W |
| 911401557642 | LS170S LED8 S 930 IP44 L5000 PRO | 30 W |
| 911401558242 | LS170S LED12 827 IP44 L5000 PRO | 41 W |
| 911401558342 | LS170S LED12 830 IP44 L5000 PRO | 41 W |
| 911401558442 | LS170S LED12 840 IP44 L5000 PRO | 41 W |
| 911401558542 | LS170S LED12 927 IP44 L5000 PRO | 41 W |
| 911401558642 | LS170S LED12 930 IP44 L5000 PRO | 41 W |
| 911401559242 | LS170S LED16 827 IP44 L5000 PRO | 52 W |
| 911401559342 | LS170S LED16 830 IP44 L5000 PRO | 52 W |
| 911401559442 | LS170S LED16 840 IP44 L5000 PRO | 52 W |
| 911401559542 | LS170S LED16 927 IP44 L5000 PRO | 52 W |

| Order Code | Full Product Name | Power Consumption |
|---|---|---|
| 911401559642 | LS170S LED16 930 IP44 L5000 PRO | 52 W |
| 911401559942 | LS170S LED20 927 IP44 L5000 PRO | 65 W |
| 911401560042 | LS170S LED20 930 IP44 L5000 PRO | 65 W |
| 911401560342 | LS170S LED9 TNW IP44 L5000 PRO | 40.5 W |
| 911401560442 | LS170S LED10 TNW IP44 L5000 PRO | 40.5 W |

| Order Code | Full Product Name | Power Consumption |
|---|---|---|
| 911401553442 | LS170S LED4 827 IP20 L5000 G2 | 18.5 W |
| 911401553542 | LS170S LED4 840 IP20 L5000 G2 | 18.5 W |
| 911401553842 | LS170S LED8 827 IP20 L5000 G2 | 34 W |
| 911401553942 | LS170S LED8 840 IP20 L5000 G2 | 34 W |

## Mechanical and Housing

| Order Code | Full Product Name | Ingress protection code |
|---|---|---|
| 911401553642 | LS170S LED4 827 IP44 L5000 G2 | IP44 |
| 911401553742 | LS170S LED4 840 IP44 L5000 G2 | IP44 |
| 911401554042 | LS170S LED8 827 IP44 L5000 G2 | IP44 |
| 911401554142 | LS170S LED8 840 IP44 L5000 G2 | IP44 |
| 911401556442 | LS170S LED8 827 IP44 L5000 PRO | IP44 |
| 911401556542 | LS170S LED8 830 IP44 L5000 PRO | IP44 |
| 911401556642 | LS170S LED8 840 IP44 L5000 PRO | IP44 |
| 911401521642 | LS170S LED20 930 IP20 L5000 HE PRO L | IP20 |
| 911401521742 | LS170S LED20 940 IP20 L5000 HE PRO L | IP20 |
| 911401528642 | LS170S LED12 865 IP20 L5000 G2 | IP20 |
| 911401528742 | LS170S LED12 930 IP20 L5000 G2 | IP20 |
| 911401528842 | LS170S LED12 940 IP20 L5000 G2 | IP20 |
| 911401554242 | LS170S LED8 S 827 IP20 L5000 G2 | IP20 |
| 911401554342 | LS170S LED8 S 840 IP20 L5000 G2 | IP20 |
| 911401554442 | LS170S LED8 S 927 IP20 L5000 G2 | IP20 |
| 911401554842 | LS170S LED12 827 IP20 L5000 G2 | IP20 |
| 911401554942 | LS170S LED12 840 IP20 L5000 G2 | IP20 |
| 911401555142 | LS170S LED12 927 IP20 L5000 G2 | IP20 |
| 911401555742 | LS170S LED16 827 IP20 L5000 G2 | IP20 |
| 911401555842 | LS170S LED16 840 IP20 L5000 G2 | IP20 |
| 911401556742 | LS170S LED8 S 827 IP20 L5000 PRO | IP20 |
| 911401556842 | LS170S LED8 S 830 IP20 L5000 PRO | IP20 |
| 911401556942 | LS170S LED8 S 840 IP20 L5000 PRO | IP20 |
| 911401557042 | LS170S LED8 S 927 IP20 L5000 PRO | IP20 |
| 911401557142 | LS170S LED8 S 930 IP20 L5000 PRO | IP20 |
| 911401557742 | LS170S LED12 827 IP20 L5000 PRO | IP20 |
| 911401557842 | LS170S LED12 830 IP20 L5000 PRO | IP20 |
| 911401557942 | LS170S LED12 840 IP20 L5000 PRO | IP20 |
| 911401558042 | LS170S LED12 927 IP20 L5000 PRO | IP20 |
| 911401558142 | LS170S LED12 930 IP20 L5000 PRO | IP20 |
| 911401558742 | LS170S LED16 827 IP20 L5000 PRO | IP20 |
| 911401558842 | LS170S LED16 830 IP20 L5000 PRO | IP20 |
| 911401558942 | LS170S LED16 840 IP20 L5000 PRO | IP20 |
| 911401559042 | LS170S LED16 927 IP20 L5000 PRO | IP20 |
| 911401559142 | LS170S LED16 930 IP20 L5000 PRO | IP20 |

| Order Code | Full Product Name | Ingress protection code |
|---|---|---|
| 911401559742 | LS170S LED20 927 IP20 L5000 PRO | IP20 |
| 911401559842 | LS170S LED20 930 IP20 L5000 PRO | IP20 |
| 911401560542 | LS170S LED8 RGBW IP44 L5000 PRO | IP44 |
| 911401554542 | LS170S LED8 S 827 IP44 L5000 G2 | IP44 |
| 911401554642 | LS170S LED8 S 840 IP44 L5000 G2 | IP44 |
| 911401554742 | LS170S LED8 S 927 IP44 L5000 G2 | IP44 |
| 911401555442 | LS170S LED12 827 IP44 L5000 G2 | IP44 |
| 911401555542 | LS170S LED12 840 IP44 L5000 G2 | IP44 |
| 911401555642 | LS170S LED12 927 IP44 L5000 G2 | IP44 |
| 911401555942 | LS170S LED16 827 IP44 L5000 G2 | IP44 |
| 911401556042 | LS170S LED16 840 IP44 L5000 G2 | IP44 |
| 911401557242 | LS170S LED8 S 827 IP44 L5000 PRO | IP44 |
| 911401557342 | LS170S LED8 S 830 IP44 L5000 PRO | IP44 |
| 911401557442 | LS170S LED8 S 840 IP44 L5000 PRO | IP44 |
| 911401557542 | LS170S LED8 S 927 IP44 L5000 PRO | IP44 |
| 911401557642 | LS170S LED8 S 930 IP44 L5000 PRO | IP44 |
| 911401558242 | LS170S LED12 827 IP44 L5000 PRO | IP44 |
| 911401558342 | LS170S LED12 830 IP44 L5000 PRO | IP44 |
| 911401558442 | LS170S LED12 840 IP44 L5000 PRO | IP44 |
| 911401558542 | LS170S LED12 927 IP44 L5000 PRO | IP44 |
| 911401558642 | LS170S LED12 930 IP44 L5000 PRO | IP44 |
| 911401559242 | LS170S LED16 827 IP44 L5000 PRO | IP44 |
| 911401559342 | LS170S LED16 830 IP44 L5000 PRO | IP44 |
| 911401559442 | LS170S LED16 840 IP44 L5000 PRO | IP44 |
| 911401559542 | LS170S LED16 927 IP44 L5000 PRO | IP44 |
| 911401559642 | LS170S LED16 930 IP44 L5000 PRO | IP44 |
| 911401559942 | LS170S LED20 927 IP44 L5000 PRO | IP44 |
| 911401560042 | LS170S LED20 930 IP44 L5000 PRO | IP44 |
| 911401560342 | LS170S LED9 TNW IP44 L5000 PRO | IP44 |
| 911401560442 | LS170S LED10 TNW IP44 L5000 PRO | IP44 |
| 911401553442 | LS170S LED4 827 IP20 L5000 G2 | IP20 |
| 911401553542 | LS170S LED4 840 IP20 L5000 G2 | IP20 |
| 911401553842 | LS170S LED8 827 IP20 L5000 G2 | IP20 |
| 911401553942 | LS170S LED8 840 IP20 L5000 G2 | IP20 |

© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.