PHILIPS

**BCP386 60LED RGBWW 24V A11 L100 DMX**

911401780612



# UniStrip G4, 695 lm, 15 W, Red, green, blue and white, Dynamic DMX, Safety class III

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

## Warnings and Safety

- For outdoor use only

## General Information

| | |
|---|---|
| Driver included | No |
| Lighting Technology | LED |
| Value ladder | Performance |

## Light Technical

| | |
|---|---|
| Luminous Flux | 695 lm |
| Correlated Color Temperature (Nom) | - |
| Luminous Efficacy (rated) (Nom) | 46 lm/W |
| Color rendering index (CRI) | - |
| Light source color | Red, green, blue and white |

## Operating and Electrical

| | |
|---|---|
| Input Voltage | 24 DC V |
| Line Frequency | - Hz |
| Power Consumption | 15 W |
| Power Factor (Fraction) | 1 |
| Connection | 2 Push-in connector 5-pole |
| Cable | 2 cables 0.15m with connectors 5-pole |
| Protection class IEC | Safety class III |

## Controls and Dimming

| | |
|---|---|
| Dimmable | Yes |
| Control interface | Dynamic DMX |

## Mechanical and Housing

| | |
|---|---|
| Housing Material | Aluminum extruded |
| Optical cover material | Polymethyl methacrylate |
| Housing Color | Dark gray |
| Overall length | 1,000 mm |
| Overall width | 25.4 mm |
| Overall height | 71.6 mm |
| Dimensions (Height x Width x Depth) | 72 x 25 x 1000 mm |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |
| Optical cover type | Clear glass |
| Net Weight (Piece) | 0.908 kg |

## Approval and Application

| | |
|---|---|
| CE mark | Yes |
| Ambient temperature range | -40 to +50 °C |

## Initial Performance (IEC Compliant)

| | |
|---|---|
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-10% |

## Product Data

| | |
|---|---|
| Order product name | BCP386 60LED RGBWW 24V A11 L100 DMX |
| Full product name | BCP386 60LED RGBWW 24V A11 L100 DMX |
| Full product code | 871951451426399 |
| Order code | 911401780612 |
| Material Nr. (12NC) | 911401780612 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8719514514263 |
| Numerator - Packs per outer box | 25 |
| EAN/UPC - Case | 8719514514263 |

## Dimensional drawing



## Related Documents

| Documents and certificates | Document Name | Download |
|---|---|---|
| Installation Instructions | BCP386 MI.pdf | Download |

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.