PHILIPS

RS350 G2 RC Rd D75 11W 27K 15D 1H

929004098710



Deep Recessed Spotlight, 11 W, 900 lm, 2700 K, High-gloss mirror, Dark gray

Aluminum die-cast, Dark gray, Power supply unit, 900 lm, 11 W, 81 lm/W, 2700 K, (0.4620, 0.4074) <5SDCM, High-gloss mirror, Clear, Polycarbonate, IP20 | Finger-protected, IK03 | 0.3 J, Safety class II, Flying leads/wires

General Information

Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Nominal lifetime	25,000 hour(s)
Switching Cycle	15,000
Warranty period	1 years

Light Technical

Luminous Flux	900 lm
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	81 lm/W
Color rendering index (CRI)	90
Number of light sources	1
Light source color	927 warm white
Optic type	High-gloss mirror
Luminaire light beam spread	15°
Photobiological safety according to EN 62471	RG1

Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Inrush current	8.5 A
Inrush time	0.18 ms
Power Consumption	11 W
Warm-up time to 60% light	<2 s
Power Factor (Fraction)	0.5
Connection	Flying leads/wires
Cable	Cable 0.1m without plug
Number of products on MCB of 16 A type B	110
Suitable for random switching	Not applicable
Protection class IEC	Safety class II

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Dark gray
Optical cover finish	Clear
Overall height	80 mm
Overall diameter	84 mm
Net weight	0.25 kg
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Net Weight (Piece)	0.250 kg

Approval and Application

Insulation Coverage Rating	Non IC Rating
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
EU RoHS compliant	Yes
Warranty	3 year(s)
EyeComfort	Yes
LED Innovations	EyeComfort
Ambient temperature range	-20 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.4620, 0.4074) <5SDCM
Power consumption tolerance	+/-10%


Over Time Performance (IEC Compliant)

Median useful life L70B50	25,000 hour(s)


Product Data

Order product name	RS350 G2 RC Rd D75 11W 27K 15D 1H
Full product name	RS350 G2 RC Rd D75 11W 27K 15D 1H
Full product code	694197061285200
Order code	929004098710
Material Nr. (12NC)	929004098710
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6941970612852
Numerator - Packs per outer box	12
EAN/UPC - Case	6941970612869


Dimensional drawing



Photometric data



General uniform lighting - RS350 G2 RC Rd D75 11W 27K 15D 1H



Light Distribution Diagram - RS350 G2 RC Rd D75 11W 27K 15D 1H

Related Documents

Photometry and lighting design	Document Name	Download
IES File	RS350-G2-RC-Rd-D75-11W-27K-15D-1H-9290040987-IES.ies	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.