PHILIPS

BCS341 60LED 40K 24V OC L100

911401779152



UniBar, 770 lm, 15 W, Neutral white, Safety class III

UniBar is a surface mounted, exterior-rated and slim sized linear LED direct view luminaire that is designed for façade and outdoor architectural lighting applications. The robust mechanical and unique optical design make it ideal for buildings facades, media facades, bridges, overpasses and any application that requires a slim linear direct view lighting solution. Direct view spread lens, through wiring for end-to-end connection and DMX control option available with up to 10 pixels (10IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations. Available in white, monochromatic colors, RGB, RGBW and tunable white.

General Information

Driver included	No
Lighting Technology	LED

Light Technical

Luminous Flux	770 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	51 lm/W
Color rendering index (CRI)	80
Light source color	Neutral white

Operating and Electrical

Input Voltage	24 DC V
Line Frequency	- Hz
Power Consumption	15 W
Power Factor (Fraction)	0.9
Connection	2 Push-in connector 2-pole
Cable	2 cables (0.2m input + 0.1m output) with connectors 2-pole
Protection class IEC	Safety class III

Controls and Dimming

Dimmable	No
Control interface	-

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Mechanical and Housing

Housing Material	Aluminum extruded
Optical cover material	Polycarbonate
Housing Color	Silver
Overall length	1,000 mm
Overall width	35 mm
Overall height	65 mm
Dimensions (Height x Width x Depth)	65 x 35 x 1000 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Opal
Net Weight (Piece)	0.886 kg

Product Data

Order product name	BCS341 60LED 40K 24V OC L100
Full product name	BCS341 60LED 40K 24V OC L100
Full product code	872016972528799
Order code	911401779152
Material Nr. (12NC)	911401779152
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169725287
Numerator - Packs per outer box	24
EAN/UPC - Case	8720169725287

Approval and Application

CE mark	Yes
Ambient temperature range	-40 to +50 °C

Dimensional drawing



Related Documents

Documents and certificates	Document Name	Download
Installation Instructions	BCS341 MI.pdf	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.