PHILIPS

Lighting



Suitable for high ceiling delivering comfortable light

GreenSpace Surface mounted

GreenSpace DN397C is brand new offering to accommodate extremely high ceiling with leading efficacy , design compactness and good reliability

Benefits

- Energy saving
- Superior optics with flexibility
- Good light quality for visual comfort
- Easy installation

Features

- High efficacy
- Two beam options
- SDCM 3, CRI >80
- Surface mounted & suspended

Application

- Airport
- Exhibition center
- Semi-outdoor

Dimensional drawing







GreenSpace Surface mounted

General Information	
Driver included	Yes
Light source replaceable	No
Number of gear units	1 unit
Service tag	Yes

Light Technical	
Beam angle of light source	120 degree(s)
Color rendering index (CRI)	≥80
Luminous Flux	12,000 lm

Operating and Electrical	
Protection class IEC	Safety class I
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Power Consumption	102 W
Suitable for random switching	No

Mechanical and Housing	
Optical cover type	Lens
Mech. impact protection code	IK06
Ingress protection code	IP65

Approval and Application	
Ambient temperature range	-20 to +40 °C
ENEC mark	-
Flammability mark	For mounting on easy flammable surfaces
Glow-wire test	Temperature 650 °C, duration 30 s

Initial Performance (IEC Compliant)	
Initial chromaticity	-
Luminous flux tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Driver failure rate at 5000 h	0.0013 %

Light Technical

Order Code	Full Product Name	Correlated Color Temperature (Nom)	Luminous Efficacy (rated) (Nom)	Optic type
911401555251	DN397C LED12/840 PSU WH WB GC	4000 K	120 lm/W	Beam angle 55°
911401555851	DN397C LED12/840 PSU WH MB GC	4000 K	120 lm/W	Beam angle 30°
911401556751	DN397C LED12/830 PSU WH WB S GC	3000 K	120 lm/W	Beam angle 55°
911401556851	DN397C LED12/840 PSU WH WB S GC	4000 K	120 lm/W	Beam angle 55°
911401557351	DN397C LED12/830 PSU WH WB GM	3000 K	115 lm/W	Beam angle 55°
911401557451	DN397C LED12/840 PSU WH WB GM	4000 K	120 lm/W	Beam angle 55°
911401557751	DN397C LED12/840 PSU WH MB GM	4000 K	120 lm/W	Beam angle 30°
911401556351	DN397C LED12/840 PSD WH WB GC	4000 K	120 lm/W	Beam angle 55°
911401556451	DN397C LED12/840 PSD BK WB GC	4000 K	120 lm/W	Beam angle 55°
911401556551	DN397C LED12/840 PSD WH MB GC	4000 K	120 lm/W	Beam angle 30°

Controls and Dimming

Order Code	Full Product Name	Dimmable	Maximum dim level
911401555251	DN397C LED12/840 PSU WH WB GC	No	Not applicable
911401555851	DN397C LED12/840 PSU WH MB GC	No	Not applicable
911401556751	DN397C LED12/830 PSU WH WB S GC	No	Not applicable
911401556851	DN397C LED12/840 PSU WH WB S GC	No	Not applicable
911401557351	DN397C LED12/830 PSU WH WB GM	No	Not applicable

Order Code	Full Product Name	Dimmable	Maximum dim level
911401557451	DN397C LED12/840 PSU WH WB GM	No	Not applicable
911401557751	DN397C LED12/840 PSU WH MB GM	No	Not applicable
911401556351	DN397C LED12/840 PSD WH WB GC	Yes	1%
911401556451	DN397C LED12/840 PSD BK WB GC	Yes	1%
911401556551	DN397C LED12/840 PSD WH MB GC	Yes	1%

Mechanical and Housing

Order Code	Full Product Name	Housing Color
911401555251	DN397C LED12/840 PSU WH WB GC	White

Order Code	Full Product Name	Housing Color
911401555851	DN397C LED12/840 PSU WH MB GC	White

GreenSpace Surface mounted

Order Code	Full Product Name	Housing Color
911401556751	DN397C LED12/830 PSU WH WB S GC	White
911401556851	DN397C LED12/840 PSU WH WB S GC	White
911401557351	DN397C LED12/830 PSU WH WB GM	White
911401557451	DN397C LED12/840 PSU WH WB GM	White

Order Code	Full Product Name	Housing Color
911401557751	DN397C LED12/840 PSU WH MB GM	White
911401556351	DN397C LED12/840 PSD WH WB GC	White
911401556451	DN397C LED12/840 PSD BK WB GC	Black
911401556551	DN397C LED12/840 PSD WH MB GC	White

Approval and Application

Order Code	Full Product Name	CE mark
911401555251	DN397C LED12/840 PSU WH WB GC	No
911401555851	DN397C LED12/840 PSU WH MB GC	No
911401556751	DN397C LED12/830 PSU WH WB S GC	No
911401556851	DN397C LED12/840 PSU WH WB S GC	No
911401557351	DN397C LED12/830 PSU WH WB GM	Yes

Order Code	Full Product Name	CE mark
911401557451	DN397C LED12/840 PSU WH WB GM	Yes
911401557751	DN397C LED12/840 PSU WH MB GM	Yes
911401556351	DN397C LED12/840 PSD WH WB GC	No
911401556451	DN397C LED12/840 PSD BK WB GC	No
911401556551	DN397C LED12/840 PSD WH MB GC	No

Over Time Performance (IEC Compliant)

Order Code	Full Product Name	Median useful life L80B50	Median useful life L90B50
911401555251	DN397C LED12/840 PSU WH WB GC	34,000 hour(s)	15,000 hour(s)
911401555851	DN397C LED12/840 PSU WH MB GC	34,000 hour(s)	15,000 hour(s)
911401556751	DN397C LED12/830 PSU WH WB S GC	34,000 hour(s)	15,000 hour(s)
911401556851	DN397C LED12/840 PSU WH WB S GC	34,000 hour(s)	15,000 hour(s)
911401557351	DN397C LED12/830 PSU WH WB GM	34,000 hour(s)	15,000 hour(s)

Order Code	Full Product Name	Median useful life L80B50	Median useful life L90B50
911401557451	DN397C LED12/840 PSU WH WB GM	34,000 hour(s)	15,000 hour(s)
911401557751	DN397C LED12/840 PSU WH MB GM	34,000 hour(s)	15,000 hour(s)
911401556351	DN397C LED12/840 PSD WH WB GC	36,000 hour(s)	17,000 hour(s)
911401556451	DN397C LED12/840 PSD BK WB GC	36,000 hour(s)	17,000 hour(s)
911401556551	DN397C LED12/840 PSD WH MB GC	36,000 hour(s)	17,000 hour(s)

© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.