PHILIPS

MASTER PL-T TOP 4 Pin

CPLTTP4P



Most reliable technology!

MASTER PL-T TOP is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The Philips amalgam technology guarantees optimum performance in applications with a wide temperature range, enabling significantly higher output and efficacy levels. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

Benefits

- Optimized lighting performance over a broad temperature range due to Philips amalgam technology
- Hot restrike; moderate light run-up after cooling-down at low temperatures
- Multiple light color choice
- Good color rendering (CRI >80)
- Dimming possible down to 30%

Applications

- Designed for general or supplementary lighting in professional and semi-professional environments
- Ideal for use in recessed or surface mounted downlighters, wall units
- First choice for long switching cycles and highest light output

Features

- 4-pin base
- Philips amalgam technology applied
- Fluorescent tri-phosphor technology
- Low light depreciation over lamp life

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Versions



LPPR PLTTOP4P 32W



LPPR PLTTOP4P 18W

Dimensional drawing



Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T TOP 18W/840/4P 1CT/5X10BOX	41 mm	71.7 mm	96.0 mm	111.7 mm



Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T TOP 32W/830/4P 1CT/5X10BOX	41 mm	98.7 mm	123.0 mm	138.7 mm
MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX	41 mm	98.7 mm	123.0 mm	138.7 mm

Light Technical

Color rendering index (CRI)	80

Controls and Dimming

Dimmable	Yes

Approval and Application

Mercury (Hg) Content (Max)	1.4 mg
Mercury (Hg) Content (Nom)	1.4 mg

General Information

Order Code	Full Product Name	Cap-Base
927911983069	MASTER PL-T TOP 32W/830/4P 1CT/5X10BOX	GX24q-3
927911984069	MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX	GX24q-3
927910884069	MASTER PL-T TOP 18W/840/4P 1CT/5X10BOX	GX24q-2

Light Technical

Order Code	Full Product Name	Luminous Flux	Color Designation	Chromaticity Coordinate X (Nom)	Chromaticity Coordinate Y (Nom)	Correlated Color Temperature (Nom)	Luminous Efficacy (Rated) (Min)
927911983069	MASTER PL-T TOP 32W/830/4P 1CT/5X10BOX	2,300 lm	Warm White (WW)	0.44	0.403	3000 K	75 lm/W
927911984069	MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX	2,300 lm	Cool White (CW)	0.38	0.38	4000 K	75 lm/W
927910884069	MASTER PL-T TOP 18W/840/4P 1CT/5X10BOX	1,160 lm	Cool White (CW)	0.38	0.38	4000 K	67 lm/W

Operating and Electrical

Order Code	Full Product Name	Power Consumption	Lamp Current (Nom)
927911983069	MASTER PL-T TOP 32W/830/4P 1CT/5X10BOX	34.5 W	0.320 A
927911984069	MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX	34.5 W	0.320 A
927910884069	MASTER PL-T TOP 18W/840/4P 1CT/5X10BOX	18.7 W	0.220 A

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
927911983069	MASTER PL-T TOP 32W/830/4P 1CT/5X10BOX	35 kWh
927911984069	MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX	35 kWh
927910884069	MASTER PL-T TOP 18W/840/4P 1CT/5X10BOX	19 kWh

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.