PHILIPS

WT140C 20S/840 WIA L600 TW3

911401893088



signify interact

CoreLine waterproof quick-fit, 13 W, L630 mm, 2000 lm, 4000 K, Wireless, Interact Ready, Symmetrical, Opal, IP65, IK08, TW3

L630 mm, Polycarbonate, White RAL 9003, Wireless driver Interact System ready, 2000 lm, 13 W, 154 lm/W, 4000 K, (0.38, 0.37) SDCM<3, Symmetrical, Opal, Polycarbonate, IP65 | Dust penetration-protected, jet-proof, IK08 | 6 J, Safety class I, Push-in connector 5-pole, Feed-through wiring 3-phase

Warnings and Safety

- UV radiation will damage the material over time resulting in loss of waterproof sealing and IP66 rating.
- Do not install the luminaire in locations where it will be exposed to direct sunlight.

General Information

Number of gear units	1 unit
Driver included	Yes
Sustainability rating	Unclassified
Value ladder	Performance
Warranty period	5 years

Light Technical

Luminous Flux	2,000 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	154 lm/W
Color rendering index (CRI)	80
Light source color	840 neutral white
Optic type	Symmetrical
Luminaire light beam spread	110°
Unified glare rating CEN	26

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	23.1 A
Inrush time	0.221 ms
Power Consumption	13 W
Power Factor (Fraction)	0.90
Connection	Push-in connector 5-pole
Cable	-
Number of products on MCB of 16 A type B	22
Suitable for random switching	Yes
Protection class IEC	Safety class I
Feed-through wiring	Feed-through wiring 3-phase

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Wireless driver Interact System ready
Control interface	Wireless
Constant light output	No
Connectivity	Interact Ready

Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Steel
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	White RAL 9003
Optical cover finish	Opal
Overall length	630 mm
Overall width	74 mm
Overall height	69 mm
Dimensions (Height x Width x Depth)	69 x 74 x 630 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [6 J]
Net Weight (Piece)	0.840 kg

Emergency Operation

Emergency lighting	-

Approval and Application

Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	KEMA Netherlands
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-25 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.38, 0.37) SDCM<3
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤3

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L90
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 100000 h	L80


Sustainability Data

Repair class	Repair Class C, the driver of this luminaire can be replaced by a service technician. Special care is required during disassembly and reassembly, and specific tools may be required. Parts and documentation are available for a period of time.
Embedded carbon (A1-A3)	7.73 kg CO_2e
Product non-virgin material ratio	16.4 %
Recyclable content ratio of the finished product	38.9 %
GWP total B6 (kg CO2eq) Declared Unit	Please calculate using your local energy mix value: Power Declared Unit (kW) * Service life (hrs) Declared Unit * Energy mix (kg CO2eq / kwh)
GWP total B6 (kg CO2eq) Functional Unit	Please calculate using your local energy mix value: Power Declared Unit (kW) * 1000 (lm) /lumen output (lm) Declared Unit * 35000 (hrs) * Energy mix (kg CO2 eq / kwh)
Non-virgin material ratio of the packaging	Cardboard > 80% recycled
Packaging Recyclable content ratio	Cardboard recycling rate > 80%
Packaging Material	Cardboard


Product Data

Order product name	WT140C 20S/840 WIA L600 TW3
Full product name	WT140C 20S/840 WIA L600 TW3
Full product code	872110370495599
Order code	911401893088
Material Nr. (12NC)	911401893088
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8721103704955
Numerator - Packs per outer box	9
EAN/UPC - Case	8721103705044

Dimensional drawing



Polar normal diagrams



Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-HUB-EPD-PHILIPS-WT140C-12-15-17-20S-840-PSU-L600-TW3-911401892488.pdf	Download
Installation Instructions	Installation-instruction-CoreLine-waterproof-quick-fit-WT140-202607.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	wt140c-20s-840-wia-l600-tw3-911401893088.ies	Download
LDT File	wt140c-20s-840-wia-l600-tw3-911401893088.ldt	Download
ROLF File	wt140c-20s-840-wia-l600-tw3-911401893088.rolfz	Download
ULD File	wt140c-20s-840-wia-l600-tw3-911401893088.uld	Download
Revit file	wt140c-20s-840-wia-l600-tw3-911401893088.zip	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.