PHILIPS

DN200 G3 LED15 840 16W D175 CN

929003272010



Essential SmartBright LED Downlight, 16 W, 1500 lm, 4000 K, Matt optic decorative, White

Plastic, White, Power supply unit (On/Off), 1500 lm, 16 W, 93 lm/W, 4000 K, (X=, 0.3863 ; Y=, 0.3863) 5SDCM, Matt optic decorative, Opal, Polycarbonate, IP20 | Finger-protected, IK03 | 0.3 J, Safety class II, Flying leads/wires

General Information

Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Lighting Technology	LED
Warranty period	1 years

Light Technical

Luminous Flux	1,500 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	93 lm/W
Color rendering index (CRI)	80
Light source color	840 neutral white
Optic type	Matt optic decorative
Luminaire light beam spread	100°

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz

Input Frequency	50 or 60 Hz
Inrush time	0.13 ms
Power Consumption	16 W
Power Factor (Fraction)	0.5
Connection	Flying leads/wires
Cable	2×0.75mm²
Suitable for random switching	Not applicable
Protection class IEC	Safety class II

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Plastic
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Steel
Housing Color	White
Optical cover finish	Opal
Overall height	35 mm
Overall diameter	190 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Net Weight (Piece)	0.162 kg

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
EU RoHS compliant	Yes
Ambient temperature range	-20 to +40 °C

Dimensional drawing



Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(X=, 0.3863 ; Y=, 0.3863) 5SDCM
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	1.2 %
Median useful life L70B50	20,000 hour(s)

Product Data

Order product name	DN200 G3 LED15 840 16W D175 CN
Full product name	DN200 G3 LED15 840 16W D175 CN
Full product code	694783049633400
Order code	929003272010
Material Nr. (12NC)	929003272010
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6947830496334
Numerator - Packs per outer box	30
EAN/UPC - Case	6947830496341

Photometric data



Light Distribution Diagram - DN200 G3 LED15 840 16W D175 CN



General uniform lighting - DN200 G3 LED15 840 16W D175 CN

Related Documents

Photometry and lighting design	Document Name	Download
IES File	DN200_G3_LED15_840_16W_D175_CN-IES.ies	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.