PHILIPS

BCS340 12LED 30K 24V OC L30

911401779042



UniBar, 145 lm, 3 W, Warm white, Safety class III

UniBar is a surface mounted, exterior-rated and slim sized linear LED direct view luminaire that is designed for façade and outdoor architectural lighting applications. The robust mechanical and unique optical design make it ideal for buildings facades, media facades, bridges, overpasses and any application that requires a slim linear direct view lighting solution. Direct view spread lens, through wiring for end-to-end connection and DMX control option available with up to 10 pixels (10IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations. Available in white, monochromatic colors, RGB, RGBW and tunable white.

General Information

Driver included	No
Lighting Technology	LED

Light Technical

Luminous Flux	145 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	48 lm/W
Color rendering index (CRI)	80
Light source color	Warm white

Operating and Electrical

Input Voltage	24 DC V
Line Frequency	- Hz
Power Consumption	3 W
Power Factor (Fraction)	0.9
Connection	2 Push-in connector 2-pole
Cable	2 cables (0.2m input + 0.1m output) with connectors 2-pole
Protection class IEC	Safety class III

Controls and Dimming

Dimmable	No
Control interface	-

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Mechanical and Housing

Housing Material	Aluminum extruded
Optical cover material	Polycarbonate
Housing Color	Silver
Overall length	300 mm
Overall width	28 mm
Overall height	65 mm
Dimensions (Height x Width x Depth)	65 x 28 x 300 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Opal
Net Weight (Piece)	0.239 kg

Product Data

Order product name	BCS340 12LED 30K 24V OC L30
Full product name	BCS340 12LED 30K 24V OC L30
Full product code	872016974894199
Order code	911401779042
Material Nr. (12NC)	911401779042
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8721103725226
Numerator - Packs per outer box	48
EAN/UPC - Case	8720169748941

Approval and Application

CE mark	Yes
Ambient temperature range	-40 to +50 °C

Dimensional drawing



© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.